



Leading Features

- ▶ High switching frequency technology-Smaller, smarter
- ▶ DRM integrated, fully comply with AS4777.2:2015
- ▶ Over 97.5% Max.efficiency
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Precise MPPT algorithm
- ▶ IP65, visually pleasing for domestic environment
- ▶ RS 485, WiFi/GPRS (optional) interface
- ▶ Numerous protection functions
- ▶ WiFi and monitoring app available
- ▶ 5 years standard warranty, 10 years optional upgrade

Model		Solis-1P3.6K-4G
Input Side (DC)		
Max. input power		4.2kW
Max. input voltage		600V
Start-up input voltage		120V
MPPT voltage range		100-500V
Max. input current		11A+11A
MPPT number/Max. input strings number		2/2
Output Side (AC)		
Rated output power		3.6kW
Max. transient power		4kW
Rated grid voltage		220/230V
Grid voltage range		160~285V(adjustable)
Rated grid frequency		50/60Hz
Operating phase		Single
Max. output current		16A
Power factor		0.8 leading ... 0.8 lagging
Total harmonic distortion (THDi)		<1.5%
DC injection current		<20mA
Grid frequency range		47-52Hz or 57-62Hz(adjustable)
Efficiency		
Max. efficiency		97.5%
EU efficiency		96.8%
MPPT efficiency		99.9%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions		310W*536H*157D(mm)
Weight		12kg
Topology		Transformerless
Self consumption		<1W(Night)
Operating ambient temperature range		-25°C~60°C
Ingress protection		IP65
Noise emission(typical)		<30 dBA
Cooling concept		Natural convection
Max. operation altitude		4000m
Designed lifetime		>20 years
Grid connection standard		EN50438, G83/2,AS4777,VDE0126-1-1,IEC61727
Relative humidity		0~100%
Safety/EMC standard		EN61000-6-1:2007; EN61000-6-3:2007 IEC62109-1-2; AS3100
Features		
DC connection		Original MC4 Connector
AC connection		IP67 rated plug
Display		LCD, 2 x 20 Z.
Interface		RS 485, WiFi/GPRS (optional)
Warranty		5~10 Years